

1326

POLYCENTRIC 4-BAR KNEE

- Polycentric 4 bar knee
- Constant friction swing phase control
- Best suited for low activity level
- Provides a high degree of safety
- Frame construction is made of superlight aluminum alloy
- Proximal attachment has 2mm of A/P, M/L slide and rotation adjustment

P/N	1326AP Pyramid Adapter	1326AL Lotus Adapter
Weight Limit	100kg / 220lbs	100kg / 220lbs
Build Height	87.3mm	93.6mm
Knee Center to Mid Dome	23mm	29.3mm
Product Weight	532g	553g
Material	Aluminum	Aluminum
Warranty	2 years	2 years



Optional Adapters:

AP = Pyramid (AK)

AL = Lotus (KD)

REPLACEMENT PARTS
P/N Description
PA13 Pyramid Adapter for: L1321, 1321, 1322, 1323, 1324, L1324 and 1326
LA13 Lotus Adapter for: L1321, 1321, 1322, 1323, 1324, L1324 and 1326

TORQUE VALUE	Torque (Nm)	Hex (mm)
M6 Cap Screw (Tube Clamp Torque Setting)	12 Nm	5mm wrench
M10 Bolt (Pyramid Center Bolt)	18 Nm	8mm wrench



PDAC approved HCPCS code(s)
• L5611 + L5850

To download PDAC Letter please visit our website at www.stngco.com