



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1209A

385mm Aluminum Tube

Weight: 227 grams
Weight Limit: 136kg / 300lbs



1209A IFU REV. D (07-11-23)



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1209A

385mm Aluminum Tube

Weight: 227 grams
Weight Limit: 136kg / 300lbs



1209A IFU REV. D (07-11-23)



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1209A

385mm Aluminum Tube

Weight: 227 grams
Weight Limit: 136kg / 300lbs



1209A IFU REV. D (07-11-23)



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1209A

385mm Aluminum Tube

Weight: 227 grams
Weight Limit: 136kg / 300lbs



1209A IFU REV. D (07-11-23)

1. Application
The 1209A, Aluminum Tube 385mm, Al is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The Tube, 385mm, Al is used with any 30mm tube clamp system. The tube must be shortened as necessary to fit the proper prosthesis height. Do not clamp the tube on a vise or similar device for it may damage the tube. The cut surface must be perpendicular to the long axis of the tube. All burrs from inner and outer surface must be removed properly. The tube must be completely inserted and in full contact with the inner base rim of the tube clamp.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

4. Declaration of Conformity
ST&G as manufacturer declares that the 1209A, Tube, 385mm, Al conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice

Tighten all the screws, which are side by side, using the torque wrench

3

1. Application
The 1209A, Aluminum Tube 385mm, Al is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The Tube, 385mm, Al is used with any 30mm tube clamp system. The tube must be shortened as necessary to fit the proper prosthesis height. Do not clamp the tube on a vise or similar device for it may damage the tube. The cut surface must be perpendicular to the long axis of the tube. All burrs from inner and outer surface must be removed properly. The tube must be completely inserted and in full contact with the inner base rim of the tube clamp.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

4. Declaration of Conformity
ST&G as manufacturer declares that the 1209A, Tube, 385mm, Al conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice

Tighten all the screws, which are side by side, using the torque wrench

3

1. Application
The 1209A, Aluminum Tube 385mm, Al is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The Tube, 385mm, Al is used with any 30mm tube clamp system. The tube must be shortened as necessary to fit the proper prosthesis height. Do not clamp the tube on a vise or similar device for it may damage the tube. The cut surface must be perpendicular to the long axis of the tube. All burrs from inner and outer surface must be removed properly. The tube must be completely inserted and in full contact with the inner base rim of the tube clamp.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.



2

1. Application
The 1209A, Aluminum Tube 385mm, Al is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The Tube, 385mm, Al is used with any 30mm tube clamp system. The tube must be shortened as necessary to fit the proper prosthesis height. Do not clamp the tube on a vise or similar device for it may damage the tube. The cut surface must be perpendicular to the long axis of the tube. All burrs from inner and outer surface must be removed properly. The tube must be completely inserted and in full contact with the inner base rim of the tube clamp.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.



2

4. Declaration of Conformity
ST&G as manufacturer declares that the 1209A, Tube, 385mm, Al conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice

Tighten all the screws, which are side by side, using the torque wrench



3

4. Declaration of Conformity
ST&G as manufacturer declares that the 1209A, Tube, 385mm, Al conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice

Tighten all the screws, which are side by side, using the torque wrench



3