



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1213T

**10 Degree Angled Tube clamp,
Ti**

Weight: 86 grams
Weight Limit: 100kg / 220lbs
Torque recommendation:
Alignment adjustment set screw: 15Nm
Pylon clamp screw: 7 Nm



1213T IFU REV. D (07-11-23)



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1213T

**10 Degree Angled Tube clamp,
Ti**

Weight: 86 grams
Weight Limit: 100kg / 220lbs
Torque recommendation:
Alignment adjustment set screw: 15Nm
Pylon clamp screw: 7 Nm



1213T IFU REV. D (07-11-23)



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1213T

**10 Degree Angled Tube clamp,
Ti**

Weight: 86 grams
Weight Limit: 100kg / 220lbs
Torque recommendation:
Alignment adjustment set screw: 15Nm
Pylon clamp screw: 7 Nm



1213T IFU REV. D (07-11-23)




stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1213T

**10 Degree Angled Tube clamp,
Ti**

Weight: 86 grams
Weight Limit: 100kg / 220lbs
Torque recommendation:
Alignment adjustment set screw: 15Nm
Pylon clamp screw: 7 Nm



1213T IFU REV. D (07-11-23)

1. Application
The Angled Tube Clamp provides the adjustable connection between the knee joint and the hip joint tube of the hip prosthesis using 30mm diameter tube. The adapter is tilted at an angle of 10° according to the tube course of typical prosthetic hip joint. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for alignment. Apply recommended torque to pylon clamp screws and alignment adjustment screws for connection. Apply locite to all screws once the alignment and connection is finalized.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

2

4. Declaration of Conformity
ST&G as supplier declares that the 1213T, Angled Tube Clamp, Ti conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice

Tighten all the screws, which are side by side, using the torque wrench

3

1. Application
The 1213T, Angled Tube Clamp, Ti is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The Angled Tube Clamp provides the adjustable connection between the pyramid of the knee joint and the hip joint tube of the hip prosthesis using 30mm diameter tube. The adapter is tilted at an angle of 10° according to the tube course of typical prosthetic hip joint. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for alignment. Apply recommended torque to pylon clamp screws and alignment adjustment screws for connection. Apply locite to all screws once the alignment and connection is finalized.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

2

4. Declaration of Conformity
Angled Tube Clamp, Ti conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice

Tighten all the screws, which are side by side, using the torque wrench

3

1. Application
The 1213T, Angled Tube Clamp, Ti is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The Angled Tube Clamp provides the adjustable connection between the knee joint and the hip joint tube of the hip prosthesis using 30mm diameter tube. The adapter is tilted at an angle of 10° according to the tube course of typical prosthetic hip joint. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for alignment. Apply recommended torque to pylon clamp screws and alignment adjustment screws for connection. Apply locite to all screws once the alignment and connection is finalized.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

2

4. Declaration of Conformity
ST&G as supplier declares that the 1213T, Angled Tube Clamp, Ti conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice

Tighten all the screws, which are side by side, using the torque wrench

3

1. Application
The 1213T, Angled Tube Clamp, Ti is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The Angled Tube Clamp provides the adjustable connection between the pyramid of the knee joint and the hip joint tube of the hip prosthesis using 30mm diameter tube. The adapter is tilted at an angle of 10° according to the tube course of typical prosthetic hip joint. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for alignment. Apply recommended torque to pylon clamp screws and alignment adjustment screws for connection. Apply locite to all screws once the alignment and connection is finalized.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

2

4. Declaration of Conformity
ST&G as supplier declares that the 1213T, Angled Tube Clamp, Ti conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice

Tighten all the screws, which are side by side, using the torque wrench

3