

1311

Weight Activated Brake Knee



P/N	1311T	1311S
Weight Limit	125kg / 275lbs	125kg / 275lbs
Build Height	42.44mm	42.44mm
Knee Center to Top	25.9mm	25.9mm
Knee Flexion	150 degrees	150 degrees
Product Weight	362g	532g
Material	Titanium	Stainless Steel
Warranty	1 year	1 year

- Single axis knee
- Stance phase friction brake
- Activated by weight bearing and designed for moderate functional demands
- Also suitable for amputees with lower functional levels who desire to avoid using a manual locking knee



PDAC approved HCPCS code(s)

- **L5812 + L5850**

REPLACEMENT PARTS

1311-1 Extension Assist Kit and Cable for P/N 1311

1313A

Manual Locking Knee – Type A



P/N	1313A
Weight Limit	90 kg / 200lbs
Build Height	39.43mm
Knee Center to Top	17.93mm
Knee Flexion	140 Degrees
Product Weight	298 g
Material	Aluminum
Warranty	1 year

- Designed for amputees with very low functional level
- Light weight manual locking knee



PDAC approved HCPCS code(s)

- **L5811**

REPLACEMENT PARTS

LY13 Lanyard for Manual Locking Knee

1313-A-N

Manual Locking Knee / Type B



P/N	1313A-N
Weight Limit	100kg / 220lbs
Knee Flexion	Degrees
Product Weight	281 g
Material	Aluminum
Warranty	2 year

- Single axis light weight manual locking knee
- Designed for beginner and elderly with low activity level
- Fully machined 7075 airplane aluminum alloy



PDAC approved HCPCS code(s)
• **L5811**

1312

Mechanical 4 Bar Knee



P/N	1312T	1312S
Weight Limit	125kg / 275lbs	125kg / 275lbs
Build Height	75.07mm	75.07mm
Knee Center to Top	15.6mm	15.6mm
Knee Flexion	110 degrees	110 degrees
Product Weight	481g	719g
Material	Titanium	Stainless Steel
Warranty	1 year	1 year

- Polycentric knee
- Frame construction is made of Titanium or Stainless steel
- Constant friction swing control
- Adjustable extension assist
- Adjustable 4 Bar stability

Suggested HCPCS code(s)

- **L5972**

1318

Single Axis Knee with Manual Lock



P/N	1318S
Weight Limit	125kg / 275lbs
Build Height	77.32mm
Knee Center to Top	22.4mm
Knee Flexion	120 degrees
Product Weight	590g
Material	Stainless Steel
Warranty	1 year

- Single Axis knee joint with adjustable manual lock
- Lower actively level
- High stance phase stability, minimal swing phase control



PDAC approved HCPCS code(s)
• **L5810 + L5850**