



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1718T

Sliding 4-Hole Receiver

Weight: 186 grams
Weight Limit: 125kg / 275lbs
Recommended Torque:
M8 alignment set screw: 15 Nm
M6 slide set screw: 5 Nm
Socket attachment flat head screw: 10 Nm



1718T IFU REV. D (07-12-23)



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1718T

Sliding 4-Hole Receiver

Weight: 186 grams
Weight Limit: 125kg / 275lbs
Recommended Torque:
M8 alignment set screw: 15 Nm
M6 slide set screw: 5 Nm
Socket attachment flat head screw: 10 Nm



1718T IFU REV. D (07-12-23)



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1718T

Sliding 4-Hole Receiver

Weight: 186 grams
Weight Limit: 125kg / 275lbs
Recommended Torque:
M8 alignment set screw: 15 Nm
M6 slide set screw: 5 Nm
Socket attachment flat head screw: 10 Nm



1718T IFU REV. D (07-12-23)




stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1718T

Sliding 4-Hole Receiver

Weight: 186 grams
Weight Limit: 125kg / 275lbs
Recommended Torque:
M8 alignment set screw: 15 Nm
M6 slide set screw: 5 Nm
Socket attachment flat head screw: 10 Nm



1718T IFU REV. D (07-12-23)



1. Application

The 1718T Sliding 4-Hole Receiver is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description

The Sliding 4 Hole Receiver permits additional sliding adjustment between the prosthetic socket and pyramid adapter. The slide adjustment range is 12,7 mm maximum or ½ in. The 4 flat head screws are tightened against 4-hole pattern socket adapter for socket attachment. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for alignment. The sliding adjustment, which is loosened and tightened using the two set screws, allows for fine tuning in any desired parallel position of the distal portion, independent of the angle of adjustment through the pyramid. Apply recommended torque to pylon clamp screws and alignment screws once the alignment and connection is finalized.

All screws should have thread locker applied and torqued to specifications.

Notice



ST&G as manufacturer declares that the 1718T, Sliding Receiver conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular user for whom it activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

4. Declaration of Conformity

Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

3. Warranty

3



1. Application

The 1718T Sliding 4-Hole Receiver is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description

The Sliding 4 Hole Receiver permits additional sliding adjustment between the prosthetic socket and pyramid adapter. The slide adjustment range is 12,7 mm maximum or ½ in. The 4 flat head screws are tightened against 4-hole pattern socket adapter for socket attachment. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for alignment. The sliding adjustment, which is loosened and tightened using the two set screws, allows for fine tuning in any desired parallel position of the distal portion, independent of the angle of adjustment through the pyramid. Apply recommended torque to pylon clamp screws and alignment screws once the alignment and connection is finalized.

All screws should have thread locker applied and torqued to specifications.

Notice



ST&G as manufacturer declares that the 1718T, Sliding Receiver conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular user for whom it activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

4. Declaration of Conformity

Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

3. Warranty

2



2. Description

The 1718T Sliding 4-Hole Receiver is to be exclusively used for the prosthetic fitting of lower extremity amputations.

4. Declaration of Conformity

The Sliding 4 Hole Receiver permits additional sliding adjustment between the prosthetic socket and pyramid adapter. The slide adjustment range is 12,7 mm maximum or ½ in. The 4 flat head screws are tightened against 4-hole pattern socket adapter for socket attachment. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for alignment. The sliding adjustment, which is loosened and tightened using the two set screws, allows for fine tuning in any desired parallel position of the distal portion, independent of the angle of adjustment through the pyramid. Apply recommended torque to pylon clamp screws and alignment screws once the alignment and connection is finalized.

All screws should have thread locker applied and torqued to specifications.

Notice



ST&G as manufacturer declares that the 1718T, Sliding Receiver conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular user for whom it activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

4. Declaration of Conformity

Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

3. Warranty

3



1. Application

The 1718T Sliding 4-Hole Receiver is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description

The Sliding 4 Hole Receiver permits additional sliding adjustment between the prosthetic socket and pyramid adapter. The slide adjustment range is 12,7 mm maximum or ½ in. The 4 flat head screws are tightened against 4-hole pattern socket adapter for socket attachment. The four set screws are used for anchoring the mating pyramid system as well as for making angular adjustment for alignment. The sliding adjustment, which is loosened and tightened using the two set screws, allows for fine tuning in any desired parallel position of the distal portion, independent of the angle of adjustment through the pyramid. Apply recommended torque to pylon clamp screws and alignment screws once the alignment and connection is finalized.

All screws should have thread locker applied and torqued to specifications.

Notice



ST&G as manufacturer declares that the 1718T, Sliding Receiver conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular user for whom it activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

4. Declaration of Conformity

Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

3. Warranty

2



2

3

All screws should have thread locker applied and torqued to specifications.

Notice



ST&G as manufacturer declares that the 1718T, Sliding Receiver conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular user for whom it activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

4. Declaration of Conformity

Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

3. Warranty

4. Declaration of Conformity

Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

3. Warranty

3

All screws should have thread locker applied and torqued to specifications.

Notice



ST&G as manufacturer declares that the 1718T, Sliding Receiver conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested for a particular user for whom it activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability. The liability shall fall upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.