



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1827T

**Diagonal 6.5mm Offset 4-Hole
Pyramid with round base, Ti**

Weight: 85 grams

Weight Limit: 170kg / 375lbs

Recommended Torque:

Socket attachment flat head screw: 10 Nm



1827T

1827T IFU REV. G (02-05-25)




stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1827T

**Diagonal 6.5mm Offset 4-Hole
Pyramid with round base, Ti**

Weight: 85 grams

Weight Limit: 170kg / 375lbs

Recommended Torque:

Socket attachment flat head screw: 10 Nm



1827T

1827T IFU REV. G (02-05-25)




stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1827T

**Diagonal 6.5mm Offset 4-Hole
Pyramid with round base, Ti**

Weight: 85 grams

Weight Limit: 170kg / 375lbs

Recommended Torque:

Socket attachment flat head screw: 10 Nm



1827T

1827T IFU REV. G (02-05-25)




stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION
Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: 1827T

**Diagonal 6.5mm Offset 4-Hole
Pyramid with round base, Ti**

Weight: 85 grams

Weight Limit: 170kg / 375lbs

Recommended Torque:

Socket attachment flat head screw: 10 Nm



1827T

1827T IFU REV. G (02-05-25)

1. Application
The 1827T, Diagonal Offset 4 Hole Pyramid with round base is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The Diagonal Offset 4 Hole Pyramid with round base is to be used to connect any modular component with 4-hole threaded system with pyramid receiver system (e.g. tube clamp). The round base reduces edge pressure square base components can generate. It has a combination 5 mm lateral, and 6.5 mm diagonal offset to help correct misalignment for prosthetic fitting.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

2

4. Environment:
Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]

5. Declaration of Conformity
ST&G as manufacturer declares that the 1827T, Diagonal Offset 4-hole Pyramid with round base conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice
All screws should have a thread locker applied and torqued to specifications.

3

1. Application
The 1827T, Diagonal Offset 4 Hole Pyramid with round base is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The Diagonal Offset 4 Hole Pyramid with round base is to be used to connect any modular component with 4-hole threaded system with pyramid receiver system (e.g. tube clamp). The round base reduces edge pressure square base components can generate. It has a combination 5 mm lateral, and 6.5 mm diagonal offset to help correct misalignment for prosthetic fitting.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

2

4. Environment:
Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]

5. Declaration of Conformity
ST&G as manufacturer declares that the 1827T, Diagonal Offset 4-hole Pyramid with round base conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice
All screws should have a thread locker applied and torqued to specifications.

3

1. Application
The 1827T, Diagonal Offset 4 Hole Pyramid with round base is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The Diagonal Offset 4 Hole Pyramid with round base is to be used to connect any modular component with 4-hole threaded system with pyramid receiver system (e.g. tube clamp). The round base reduces edge pressure square base components can generate. It has a combination 5 mm lateral, and 6.5 mm diagonal offset to help correct misalignment for prosthetic fitting.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

2

4. Environment:
Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]

5. Declaration of Conformity
ST&G as manufacturer declares that the 1827T, Diagonal Offset 4-hole Pyramid with round base conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice
All screws should have a thread locker applied and torqued to specifications.

3

1. Application
The 1827T, Diagonal Offset 4 Hole Pyramid with round base is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. Description
The Diagonal Offset 4 Hole Pyramid with round base is to be used to connect any modular component with 4-hole threaded system with pyramid receiver system (e.g. tube clamp). The round base reduces edge pressure square base components can generate. It has a combination 5 mm lateral, and 6.5 mm diagonal offset to help correct misalignment for prosthetic fitting.

3. Warranty
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers 2 years warranty.

2

4. Environment:
Store at room temperature, and avoid extremely hot, cold, or moist storage environments Storage Temperature Range: between temperatures of -20°C to 80°C [-4°F and 176°F]

5. Declaration of Conformity
ST&G as manufacturer declares that the 1827T, Diagonal Offset 4-hole Pyramid with round base conforms to the requirements of Council EU 2017/745 (MDR). ST&G products are manufactured and tested upon those that resale/provide the product to anyone other than the original user delivered to. Not to be resold by private party.

Notice
All screws should have a thread locker applied and torqued to specifications.

3