



stngco.com

CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: P242S

**22mm Tube Clamp with Standard
Pyramid Receiver, SS**

Weight: 94 grams

Weight Limit: 55 kg/ 122 lbs

Torque recommendation:

Alignment adjustment set screw – 10 Nm

Pylon clamp screw – 4 Nm



P242S

P242S IFU REV B (8-1-25)



stngco.com


CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: P242S

**22mm Tube Clamp with Standard
Pyramid Receiver, SS**

Weight: 94 grams

Weight Limit: 55 kg/ 122 lbs

Torque recommendation:

Alignment adjustment set screw – 10 Nm

Pylon clamp screw – 4 Nm



P242S

P242S IFU REV B (8-1-25)



stngco.com


CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: P242S

**22mm Tube Clamp with Standard
Pyramid Receiver, SS**

Weight: 94 grams

Weight Limit: 55 kg/ 122 lbs

Torque recommendation:

Alignment adjustment set screw – 10 Nm

Pylon clamp screw – 4 Nm



P242S

P242S IFU REV B (8-1-25)



stngco.com


CORPORATE OFFICE

2691 Saturn Street, Brea, CA 92821
Tel: (714) 524-0663, Fax: (714) 364-8113



ST&G CORPORATION

Rm. 911 43, Yangsan-ro
Yeongdeungpo-gu, Seoul, Korea



MDSS GmbH

Schiffgraben 41, 30175 Hannover, Germany



REF: P242S

**22mm Tube Clamp with Standard
Pyramid Receiver, SS**

Weight: 94 grams

Weight Limit: 55 kg/ 122 lbs

Torque recommendation:

Alignment adjustment set screw – 10 Nm

Pylon clamp screw – 4 Nm



P242S

P242S IFU REV B (8-1-25)

1. **Application**
The P242S, SS 22mm Tube Clamp with Standard Pyramid Receiver is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. **Description**
The Tube Clamp is used to connect any component with another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability.

6. **Useful Life**
Service life of the product is covered by the warranty period.

7. **Disposal**
The device and its packaging must be disposed of in accordance with respective national/local environmental regulations.

***Notice**

Tighten all the screws, which are side by side, using the torque wrench

Do not store in wet or very hot environment
Storage Temperature Range: between 20°C to 80°C [-4°F and 176°F]
cold, or moist storage environments
Store at room temperature, and avoid extremely hot, year warranty on this product.

3. **Warranty**
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers a 2 year warranty on this product.

4. **Environment:**
Store at room temperature, and avoid extremely hot, cold, or moist storage environments
Storage Temperature Range: between 20°C to 80°C [-4°F and 176°F]
Do not store in wet or very hot environment

2

1. **Application**
ST&G as manufacturer declares that the P242S, SS 22mm Tube Clamp with Standard Pyramid Receiver, conforms to the requirements of Council EU 2017/745 (EU). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability.

6. **Useful Life**
Service life of the product is covered by the warranty period.

7. **Disposal**
The device and its packaging must be disposed of in accordance with respective national/local environmental regulations.

***Notice**

Tighten all the screws, which are side by side, using the torque wrench

Do not store in wet or very hot environment
Storage Temperature Range: between 20°C to 80°C [-4°F and 176°F]
cold, or moist storage environments
Store at room temperature, and avoid extremely hot, year warranty on this product.

3. **Warranty**
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers a 2 year warranty on this product.

4. **Environment:**
Store at room temperature, and avoid extremely hot, cold, or moist storage environments
Storage Temperature Range: between 20°C to 80°C [-4°F and 176°F]
Do not store in wet or very hot environment

3

1. **Application**
ST&G as manufacturer declares that the P242S, SS 22mm Tube Clamp with Standard Pyramid Receiver, conforms to the requirements of Council EU 2017/745 (EU). ST&G products are manufactured and tested for a particular weight and activity impact level. Use by another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability.

6. **Useful Life**
Service life of the product is covered by the warranty period.

7. **Disposal**
The device and its packaging must be disposed of in accordance with respective national/local environmental regulations.

***Notice**

Tighten all the screws, which are side by side, using the torque wrench

Do not store in wet or very hot environment
Storage Temperature Range: between 20°C to 80°C [-4°F and 176°F]
cold, or moist storage environments
Store at room temperature, and avoid extremely hot, year warranty on this product.

3. **Warranty**
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers a 2 year warranty on this product.

4. **Environment:**
Store at room temperature, and avoid extremely hot, cold, or moist storage environments
Storage Temperature Range: between 20°C to 80°C [-4°F and 176°F]
Do not store in wet or very hot environment

3

1. **Application**
The P242S, SS 22mm Tube Clamp with Standard Pyramid Receiver is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. **Description**
The Tube Clamp is used to connect any component with another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability.

6. **Useful Life**
Service life of the product is covered by the warranty period.

7. **Disposal**
The device and its packaging must be disposed of in accordance with respective national/local environmental regulations.

***Notice**

Tighten all the screws, which are side by side, using the torque wrench

Do not store in wet or very hot environment
Storage Temperature Range: between 20°C to 80°C [-4°F and 176°F]
cold, or moist storage environments
Store at room temperature, and avoid extremely hot, year warranty on this product.

3. **Warranty**
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers a 2 year warranty on this product.

4. **Environment:**
Store at room temperature, and avoid extremely hot, cold, or moist storage environments
Storage Temperature Range: between 20°C to 80°C [-4°F and 176°F]
Do not store in wet or very hot environment

2

1. **Application**
The P242S, SS 22mm Tube Clamp with Standard Pyramid Receiver is to be exclusively used for the prosthetic fitting of lower extremity amputations.

2. **Description**
The Tube Clamp is used to connect any component with another user for whom it was not originally manufactured may cause injury and voids any written or implied warranty, or liability.

6. **Useful Life**
Service life of the product is covered by the warranty period.

7. **Disposal**
The device and its packaging must be disposed of in accordance with respective national/local environmental regulations.

***Notice**

Tighten all the screws, which are side by side, using the torque wrench

Do not store in wet or very hot environment
Storage Temperature Range: between 20°C to 80°C [-4°F and 176°F]
cold, or moist storage environments
Store at room temperature, and avoid extremely hot, year warranty on this product.

3. **Warranty**
Warranty applies only when the product is used as intended without modification, following all manufacturer's recommendations. ST&G offers a 2 year warranty on this product.

4. **Environment:**
Store at room temperature, and avoid extremely hot, cold, or moist storage environments
Storage Temperature Range: between 20°C to 80°C [-4°F and 176°F]
Do not store in wet or very hot environment

2

3