



Linear Offset 4-Hole Pyramid, Ti

Instructions For Use

1717



1717S



1717T



1717T-B

1. Application & Description

- The 1717S/T Offset 4-Hole Pyramid is designed exclusively for prosthetic fittings of lower extremity amputations.
- It is suitable for both Transtibial and Transfemoral sockets connecting a 4-Hole mount to a pyramid receiver where 7mm of linear translation is needed.

2. Technical Specifications

P/N	Material	Build Height	Weight	Weight Limit
1717S	Stainless Steel	9mm	114g	136kg/300lbs
1717T	Titanium	9mm	90g	170kg/375lbs
1717T-B	Titanium	9mm	90g	170kg/375lbs

- **Offset:** 7mm linear
- **Recommended Torque:**
- **M6 Flat Head Screw Torque:**
 - (Titanium/ Stainless Steel): 10 Nm

3. Installation Overview

- **Attachment:** The plate is anchored to the prosthetic socket using a 4-hole connector system and four socket mounting screws.
- **Compatibility:** Connects any modular component featuring a 4-hole threaded system to a pyramid receiver system (such as a tube clamp).
- **Fastening:** Tighten all screws that are side by side using a torque wrench

4. Safety & Environment

- **Temperature Range:** Between -20°C to 80°C (-4°F to 176°F).
- Rinse with clean water if exposed to salty, chlorinated, or otherwise potentially corrosive liquids.
- **Storage:** Store at room temperature; avoid wet, very hot, or extremely cold environments.
- **Warranty:** 2 years, provided it is used as intended without modification, and only for the original intended user
- Do not reuse on another prosthesis.
- **Conformity:** This product meets the requirements Council EU 2017/745 (MDR) for medical products. This product has been classified as a class I product according to the classification criteria outlined in appendix IX of the guidelines. Please keep this manual in safe place for future reference.



1717 IFU REV.B (6-16-2026)

Specifications subject to change.